











COMPOSITION

Syncon laminate 0.7 mm thick.

RECOMMENDED APPLICATIONS

Syncon Laminates offers matching laminates from the Syncon range, with the same finish for application in furniture and interior decoration.

Physical and mechanical properties

Property	Result	Standard
 Stain resistance	Class 5	EN 14323
 Cold liquid resistance	Class 5	EN 14323
 Crack resistance	Class 5	EN 14323
 Light fastness	Blue: >6 Gray: 5	EN 14323
 Dry heat resistance	Class 5	EN 12722
 Damp heat resistance	Class 5	EN 12721
 Scratch resistance (diamond tip 0,09 mm)	> 2 N	EN 438-2
 Abrasion resistance	Class 3A	EN 14323
 Steam resistance	Class 5	EN 14323
 Impact resistance	140 cm	EN 14323

USE RECOMMENDATIONS

Storage and cleaning




10°C
40°C

Recommended storage temperature: 10°C - 40°C



30%
70%

Recommended storage humidity: 30% - 70%



Do not expose to sunlight and others sources of heat for long time.



Clean with a soft cloth using water with mild soap.



Do not use any cleaners containing alcohol, solvents or abrasives.

Notes

The applicable defect assessment conditions and quality standards are those defined in the Synchron board data sheet (see corresponding data sheet).
